

View Online at <https://aerobasegroup.com/nsn/4820-01-033-2869>

Thread Class:

3b

End Connection Quantity:

3

Valve Discharge Flow Rate:

6.0 gallons per minute

End Application:

9h8-35-10-3 fig 5

Current Rating In Amps:

0.5

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.750 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Flow Pattern Quantity:

3

Spool Position Quantity:

2

Spool Quantity:

1

Special Features:

Manufacturers suggested name is valve assembly, 3 way, 2 position, pilot operated, auxiliary manual; fluid medium mil-h-46170; proof pressure 4500 psig, burst pressure 7500 psig; ports per ms33649-8; temp range -65 to +160 degrees feh; dimensions: length 5.10 to 5.30 inchs, width 1.75 inch, height 4.01 to 4.21 inches; wt 1.14 lbs

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A506h0