

View Online at <https://aerobasegroup.com/nsn/4820-01-033-2869>

**Thread Class:**

3b

**End Connection Quantity:**

3

**Valve Discharge Flow Rate:**

6.0 gallons per minute

**End Application:**

9h8-35-10-3 fig 5

**Current Rating In Amps:**

0.5

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.750 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

160.0 degrees fahrenheit hydraulic fluid, petroleum base

**Voltage In Volts And Current Type:**

18.0 dc and 30.0 dc

**Flow Pattern Quantity:**

3

**Spool Position Quantity:**

2

**Spool Quantity:**

1

**Special Features:**

Manufacturers suggested name is valve assembly, 3 way, 2 position, pilot operated, auxiliary manual; fluid medium mil-h-46170; proof pressure 4500 psig, burst pressure 7500 psig; ports per ms33649-8; temp range -65 to +160 degrees feh; dimensions: length 5.10 to 5.30 inchs, width 1.75 inch, height 4.01 to 4.21 inches; wt 1.14 lbs

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A506h0