

View Online at <https://aerobasegroup.com/nsn/4820-01-038-6973>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit 2nd response

Connection Style:

Flareless 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Special Features:

Supports grumman a-10 aircraft

Material:

Steel comp 440c flow control device

Material Specification:

Qq-s-763, class 440c federal specification single material response flow control device

Media For Which Designed:

Oil, hydraulic 1st response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.