NSN 4820-01-043-9706

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-043-9706 **Body Material:** Aluminum **Body Style:** Cross Stem Material: Steel, corrosion resisting Media For Which Designed: Air **First End Connection Type:** Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt **First End Thread Direction:** Right-hand Second End Relationship With First End: Not identical **Second End Connection Type:** Threaded internal pipe **Second End Style Designator:** Plain Second End Thread Size And Series/type Designator: 1/8-27 npt **Second End Thread Direction:** Right-hand Third End Relationship With Preceding Ends: Identical with first end Fourth End Relationship With Preceding Ends: Identical with second end **Seat Material:** Aluminum **First Connection Face To Centerline Distance:** 0.781 inches **Second Connection Face To Centerline Distance:** 0.781 inches **Third Connection Face To Centerline Distance:** 0.781 inches **Err Default:** Err default **Packing Material:**

Rubber, buna-n

NSN 4820-01-043-9706

Fluid Pressure Regulating Valve - Page 2 of 2



Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, buna-n
End Connection Quantity:
4
Renewable Seat Ring Type:
Threaded
Outlet Pressure Range:
+0.0/+125.0 pounds per square inch
Regulation Type:
Manual single stage
Manual Control Method:
Knob
Valve Stem Design:
Single seat
Valve Loading Method:
Spring
Maximum Inlet Pressure Rating:
300.0 pounds per square inch
Filter:
Not included
End Application:
Arsr1
Tempurature Rating:
Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A21100