

View Online at <https://aerobasegroup.com/nsn/4820-01-044-0432>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bolt Hole Quantity:

6 2nd end

Maximum Operating Temp:

275.0 degrees fahrenheit single response

End Application:

Acft, type f-16

Connection Style:

External seat for gasket seal (boss) 1st end

Valve Operation Method:

Manual

Flange Shape:

Round 2nd end

Connection Type:

Threaded external boss 1st end

Maximum Operating Pressure:

60.0 pounds per square inch 1st response

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter:

2.000 inches 2nd end

Thickness:

0.080 inches 2nd end

Bolt Hole Diameter:

0.128 inches 2nd end

Bolt Circle Diameter:

1.500 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.132 inches 2nd end

Raised Face Diameter:

1.000 inches 2nd end

Special Features:

Body style: straight through

Material:

Rubber packing

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Thread Series Designator:

Unjf 1st end

Fsc Application Data:

Fuselage water drain system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530c0

Mil-std (military Standard):

Mil-a-8625 spec.