NSN 4820-01-044-0432

Poppet Drain Cock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-044-0432

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bolt Hole Quantity:
6 2nd end
Maximum Operating Temp:
275.0 degrees fahrenheit single response
End Application:
Acft, type f-16
Connection Style:
External seat for gasket seal (boss) 1st end
Valve Operation Method:
Manual
Flange Shape:
Round 2nd end
Connection Type:
Threaded external boss 1st end
Maximum Operating Pressure:
60.0 pounds per square inch 1st response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter:
2.000 inches 2nd end
Thickness:
0.080 inches 2nd end
Bolt Hole Diameter:
0.128 inches 2nd end
Bolt Circle Diameter:
1.500 inches 2nd end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.132 inches 2nd end
Raised Face Diameter:
1.000 inches 2nd end
Special Features:
Body style: straight through

NSN 4820-01-044-0432

Poppet Drain Cock - Page 2 of 2

Mil-a-8625 spec.



Material:
Rubber packing
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Thread Series Designator:
Unjf 1st end
Fsc Application Data:
Fuselage water drain system
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A530c0
Mil-std (military Standard):