## NSN 4820-01-044-3895



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-044-3895 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 480.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 

3000.0 pounds per square inch single response

**Thread Size:** 

0.438 inches all ends

Seat Angle:

37.0 degrees all ends

**Opening Pressure Setting:** 

1.0 pounds per square inch

Material:

Aluminum alloy 2024

**Material Specification:** 

Qq-a-225/6, alloy 2024, t4 federal specification single material response

Media For Which Designed:

Oil, lubricating, diester base 2nd response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:** 

Straight thru

**Thread Series Designator:** 

Unjf all ends

Shelf Life:

N/a

## NSN 4820-01-044-3895

Check Valve - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.