
NSN 4820-01-045-2564

Safety Relief Valve - Page 1 of 2



AeroBase Group

Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Bolted **Disk Loading Method:** Spring **Bolt Hole Quantity:** 8 all ends Maximum Operating Temp: 150.0 degrees fahrenheit single response **End Application:** Ship, ohio class ss (trident) Valve Operation Method: Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Opening Pressure Setting:

150.0 pounds per square inch

Outside Diameter:

6.625 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

6.000 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.500 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

NSN 4820-01-045-2564

Safety Relief Valve - Page 2 of 2



Material Specification:

Qq-n-288 federal specification single material response seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0