Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-050-5716

| View Online at https://aerobasegroup.com/nsn/4820-01-050-5 |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Pressure seal, ring type |
| Renewable Seat Ring Type: |
| Pressed-in |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Connection Style: |
| G46b plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Thread Size: |
| 0.125 inches 1st end |
| Opening Pressure Setting: |
| 1.5 pounds per square inch |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response |
| Media For Which Designed: |
| Hydrogen 5th response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |