

View Online at <https://aerobasegroup.com/nsn/4820-01-051-8215>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

G46a plain (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Adjustable Pressure Range:

+25.0/+75.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.563 inches 1st end

Opening Pressure Setting:

50.0 pounds per square inch

Material:

Rubber butadiene-acrylonitrile class nbr seat

Material Specification:

Qq-a-225/6 federal specification single material response body

Media For Which Designed:

Helium 5th response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625a type i military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Unjf 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625a spec.