NSN 4820-01-052-0070



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-052-0070 **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **End Application:** Aux/amphib ship maint strategy program **Connection Style:** G46a plain (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 2nd end Thready Qty Per Inch (tpi): 14 2nd end **Maximum Operating Pressure:** 230.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 200.0 pounds per square inch Material: Steel comp 316 flow control device **Material Specification:** Qq-c-390, alloy d4/d/ federal specification single material response body Media For Which Designed: Air single response **Style Designator:**

Style Designator:
Err-090
Thread Series Designator:
Uns all ends
Furnished Items And Quantity:
2 nut and 2 tailpiece
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-052-0070

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0