# NSN 4820-01-052-0070

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-052-0070

# Thread Direction:

Right-hand all ends

## **Flow Control Device:**

Disk

## Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Threaded

#### **Disk Loading Method:**

Spring

## **End Application:**

Aux/amphib ship maint strategy program

## Connection Style:

G46a plain (tube) all ends

## Valve Operation Method:

Automatic

# **Connection Type:**

Threaded external tube 2nd end

# Thready Qty Per Inch (tpi):

14 2nd end

# Maximum Operating Pressure:

230.0 pounds per square inch single response

# Thread Size:

0.750 inches 1st end

## **Opening Pressure Setting:**

200.0 pounds per square inch

## Material:

Steel comp 316 flow control device

## Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body

## Media For Which Designed:

Air single response

## Style Designator:

Err-090

## **Thread Series Designator:**

Uns all ends

## Furnished Items And Quantity:

2 nut and 2 tailpiece

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 4820-01-052-0070

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

