

View Online at <https://aerobasegroup.com/nsn/4820-01-053-5083>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk or stem

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

314.0 cubic feet per minute

Maximum Operating Temp:

165.0 degrees fahrenheit single response

Connection Style:

G46b plain (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe all ends

Maximum Operating Pressure:

125.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Material:

Steel comp 303 stem

Material Specification:

Qq-s-764, comp 303-canceled federal specification single material response stem

Media For Which Designed:

Air single response

Style Designator:

Err-090

Test Data Document:

34494-20304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0