## NSN 4820-01-054-6657

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-054-6657

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
G43 external seat for gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss 1st end
Maximum Operating Pressure:
30.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
19.0 pounds per square inch
Special Features:
6th media oxygen, gaseous
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/4, t4 federal specification single material response
Media For Which Designed:
Nitrogen, gaseous 5th response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-054-6657

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0