Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-058-0917

Body Material. Brass Body Style: Straight thru Media For Which Designed: Water First End Connection Type: First End Connection Type: First End Connection Type: First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Dis0.0 pounds per square inch Fitter: Not included Tempurature Rating: 175.0 degrees fahrenheit Sheff Life: N/a Unit Of Measure: 	Body Material:
Bady Style: Straight thru Media For Which Designed: Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Intel Pressure Rating: 105.0 pounds per square inch Futer: Not included Empurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	•
Straight thu Media For Which Designed: Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 105.0 pounds per square inch Filter: Not included Finder: Not included Tempurature Rating: 175.0 degrees fahrenheit Sheft Life: N/a Unit Of Measure:	
Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Resead-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure: Valve	
Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Intel Pressure Rating: 105.0 pounds per square inch Outed Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	-
First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Ditto Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Sheff Life: N/a Unit Of Measure:	-
Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Dist. Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Sheff Life: N/a Unit Of Measure:	
First End Style Designator: Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 105.0 pounds per square inch Filter: Not included Filter: Not included Sheff Life: N/a Unt Of Measure: T	
Plain First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
First End Thread Size And Series/type Designator: 0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Vaive Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Fempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
0.500-14 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Fingurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Cuttet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 150.0 pounds per square inch Filter: Not included Fempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	-
Second End Relationship With First End: Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 150.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Identical Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Fempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	-
Flow Control Device: Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Fempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Disk, top guided Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Flow Control Device Material: Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Rubber, synthetic End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 150.0 pounds per square inch Filter: Not included Finepurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
End Connection Quantity: 2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Finpurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
2 Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Finpurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	-
Renewable Seat Ring Type: Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	End Connection Quantity:
Pressed-in Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	2
Regulation Type: Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Automatic double stage Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Pressed-in
Valve Loading Method: Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	
Bellows and spring Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Automatic double stage
Maximum Inlet Pressure Rating: 150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Valve Loading Method:
150.0 pounds per square inch Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Bellows and spring
Outlet Pressure Setting: 105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Maximum Inlet Pressure Rating:
105.0 pounds per square inch Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	150.0 pounds per square inch
Filter: Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Outlet Pressure Setting:
Not included Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	105.0 pounds per square inch
Tempurature Rating: 175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Filter:
175.0 degrees fahrenheit Shelf Life: N/a Unit Of Measure:	Not included
Shelf Life: N/a Unit Of Measure:	Tempurature Rating:
N/a Unit Of Measure: 	175.0 degrees fahrenheit
Unit Of Measure:	Shelf Life:
	N/a
	Unit Of Measure:
Demilitarization:	
	Demilitarization:

No

NSN 4820-01-058-0917

Fluid Pressure Regulating Valve - Page 2 of 2

Fiig: A21100

