## NSN 4820-01-058-7687

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-058-7687 **Thread Class:** 2a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring **Maximum Operating Temp:** 100.0 degrees fahrenheit single response **Connection Style:** External seat for gasket seal (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 6000.0 pounds per square inch single response **Thread Size:** 1.188 inches all ends Material: Steel comp 416 flow control device or steel comp 420 flow control device **Material Specification:** Fed-std-66, comp 416 federal standard 1st material response flow control device or fed-std-66, aisi 420/sae 51420 federal standard 2nd material response flow control device Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment: Passivate Style Designator:** Straight thru **Thread Series Designator:** Un all ends Shelf Life:

Demilitarization:

**Unit Of Measure:** 

No

N/a

## NSN 4820-01-058-7687

Check Valve - Page 2 of 2



Fiig:

A530b0