

View Online at <https://aerobasegroup.com/nsn/4820-01-059-1173>

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 2nd end

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

Plain (tube) 1st end

Width:

2.188 inches 2nd end

Length:

2.188 inches 2nd end

Valve Operation Method:

Automatic

Flange Shape:

Rectangular with holes 2nd end

Connection Type:

Unthreaded external tube 1st end

Mounting Position:

Horizontal

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thickness:

0.300 inches 2nd end

Bolt Hole Diameter:

2.500 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 2nd end

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 1st end

Flange Face Design:

Plain 2nd end

Outside Diameter Tube Accommodated:

1.520 inches 1st end

Material:

Rubber seat

Material Specification:

Qq-a-225/8, alloy 6061, t651 federal specification single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Straight thru

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-r-25897 spec.