## NSN 4820-01-059-1173

Check Valve - Page 1 of 2

Flow Control Device:

**Disk Loading Method:** 

Poppet

Spring



View Online at https://aerobasegroup.com/nsn/4820-01-059-1173

1 6	
Bolt Hole Quantity:	
4 2nd end	
Maximum Operating Temp:	
400.0 degrees fahrenheit single response	
Connection Style:	
Plain (tube) 1st end	
Width:	
2.188 inches 2nd end	
Length:	
2.188 inches 2nd end	
Valve Operation Method:	
Automatic	
Flange Shape:	
Rectangular with holes 2nd end	
Connection Type:	
Unthreaded external tube 1st end	
Mounting Position:	
Horizontal	
Maximum Operating Pressure:	
400.0 pounds per square inch single response	
Thickness:	
0.300 inches 2nd end	
Bolt Hole Diameter:	
2.500 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Length:	
1.656 inches 2nd end	
Center To Center Distance Between Bolt Holes Along Width:	
1.656 inches 1st end	
Flange Face Design:	
Plain 2nd end	
Outside Diameter Tube Accommodated:	
1.520 inches 1st end	
Material:	
Rubber seat	
Material Specification:	
Qq-a-225/8, alloy 6061, t651 federal specification single material response body	
Media For Which Designed:	
Fuel/oil, hydrocarbon 2nd response	

## NSN 4820-01-059-1173

Check Valve - Page 2 of 2

Mil-r-25897 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Straight thru
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A530b0
Mil-std (military Standard):