NSN 4820-01-062-3499

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-062-3499

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Adjustable Pressure Range:
+115.0/+250.0 pounds per square inch
Maximum Operating Pressure:
3600.0 pounds per square inch single response
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Material:
Stainless steel flow control device
Media For Which Designed:
Air 1st response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Angle
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-01-062-3499

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.