NSN 4820-01-063-6468

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-063-6468

View Online at https://aerobasegroup.com/nsn/4820-01-063-6
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
24.0 degrees all ends
Material:
Stainless steel body
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unj all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarization:

No

NSN 4820-01-063-6468

Restrictor Check Valve - Page 2 of 2

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.

