NSN 4820-01-065-4280

Ball Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-065-4280

| view Online at https://aerobasegroup.com/nsn/4 |
|--|
| Thread Class: |
| 2a all ends |
| Thread Direction: |
| Right-hand all ends |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Maximum Operating Temp: |
| 150.0 degrees fahrenheit single response |
| Connection Style: |
| G46a plain (tube) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded external tube all ends |
| Mounting Facility: |
| Panel |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.250 inches all ends |
| Special Features: |
| Incl 2 sleeve |
| Material: |
| Plastic polyurethane packing |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unf all ends |
| Furnished Items And Quantity: |
| 2 ferrule and 2 nut |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |