

View Online at <https://aerobasegroup.com/nsn/4820-01-068-8606>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Maximum Operating Temp:**

300.0 degrees fahrenheit single response

**Connection Style:**

Flared (tube) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

12 all ends

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.312 inches all ends

**Seat Angle:**

37.0 degrees all ends

**Special Features:**

Non-standard cracking pressure 5 psi

**Material:**

Aluminum alloy 2024 seat

**Material Specification:**

Qq-a-225/6, alloy 2024, t4 federal specification 1st material response flow control device or qq-a-225/6, alloy 2024, t351 federal specification 2nd material response flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Unj all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0

**Mil-std (military Standard):**

Mil-a-8625 spec.