NSN 4820-01-069-1088

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-069-1088

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

G46a plain (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Opening Pressure Setting:

0.5 pounds per square inch

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6, alloy 2024, t4 federal specification all material responses

Media For Which Designed:

Air 1st responsealcohol, ethyl 2nd responseammonia, gaseous 3rd responsefuel/oil, hydrocarbon 4th responsehelium 5th response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-f-f-14072, finish e511 military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-01-069-1088

Safety Relief Valve - Page 2 of 2

Fiig: A046b0 Mil-std (military Standard):

Mil-f-f-14072 spec.

