NSN 4820-01-075-6204

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-075-6204 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 85.0 degrees celsius single response **Connection Style:** G46b plain (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 20 all ends Adjustable Pressure Range: +85.0/+90.0 pounds per square inch **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Material: Aluminum alloy 2024 body **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unjf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-075-6204

Safety Relief Valve - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.