NSN 4820-01-079-9011

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-079-9011

Tion Control Boxico.
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+35.0/+44.0 pounds per square inch
Maximum Operating Pressure:
275.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Face To Face Distance:
3.344 inches
Thickness:
0.440 inches all ends
First Connection Face To Centerline Distance:
3.344 inches
Bolt Hole Diameter:
0.620 inches all ends
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
2.380 inches all ends
Flange Face Design:
Raised with curve and radius all ends
Raised Face Height:
0.180 inches all ends

NSN 4820-01-079-9011

Safety Relief Valve - Page 2 of 2



Raised Face Diameter:
1.190 inches all ends
Material:
Steel stem
Material Specification:
Qq-s-763 federal specification single material response stem
Media For Which Designed:
Gas, natural single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·

A046b0