

View Online at https://aerobasegroup.com/nsn/4820-01-082-0768

| Body Material:  |
|---|
| Aluminum alloy  |
| Outside Surface Treatment:                                      |
| Anodized, mil-a-8625, type 2                                    |
| Body Style:   |
| Cross give "adqm" "adqn" "adqp" "adqq" only if flanged all ends |
| Tempurature Rating:   |
| 150.0 degrees fahrenheit  |
| First End Connection Type:                                      |
| Threaded internal boss  |
| Second End Relationship With First End:                         |
| Identical   |
| Third End Relationship With Preceding Ends:                     |
| Identical with first end  |
| Fourth End Relationship With Preceding Ends:                    |
| Identical with first end  |
| First Connection Face To Centerline Distance:                   |
| 1.500 inches  |
| Second Connection Face To Centerline Distance:                  |
| 1.500 inches  |
| Third Connection Face To Centerline Distance:                   |
| 1.500 inches  |
| Err Default:  |
| Err default   |
| Flow Control Device:  |
| Diaphragm   |
| Flow Control Device Material:                                   |
| Silicone  |
| End Connection Quantity:  |
| 4   |
| Opening Pressure Setting:                                       |
| 20.0 pounds per square inch                                     |
| Adjustable Pressure Range:                                      |
| +0.0/+2.0 pounds per square inch                                |
| Valve Discharge Flow Rate:                                      |
| 40.0 cubic feet per minute                                      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

No

## NSN 4820-01-082-0768

Pressure And Temperature Relief Valve - Page 2 of 2

**Fiig:** A07100

