NSN 4820-01-086-2835

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-086-2835

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

G50 external seat for gasket seal (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss all ends

Thready Qty Per Inch (tpi):

12 all ends

Adjustable Pressure Range:

+10.0/+14.0 pounds per square inch

Maximum Operating Pressure:

750.0 pounds per square inch single response

Thread Size:

2.250 inches all ends

Material:

Steel comp 303 stem

Material Specification:

Qq-s-764, cl303 federal specification single material response stem

Media For Which Designed:

Air single response

Style Designator:

Err-090

Thread Series Designator:

Un all ends

Shelf Life:

N/a

NSN 4820-01-086-2835

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

