NSN 4820-01-086-7919

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-086-7919

Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
1.000 gallons per minute
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Sturgeon class ssn637)
Connection Style:
Reduced socket with one brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+25.0/+29.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Water, fresh single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 wrench and 2 nut and 2 tailpiece
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-01-086-7919

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0