## NSN 4820-01-089-9114

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-089-9114

Thread Class:
2b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+630.0/+1020.0 pounds per square inch
Maximum Operating Pressure:
3600.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Material:
Steel comp 303 flow control device
Material Specification:
Qq-s-763, class 303, cond a federal specification single material response flow control device
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Err-090
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-089-9114

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0