Check Valve - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4820-01-089-9221

Unit Of Measure: Demilitarization:	Thread D	in at in a
Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure:		
Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 	-	
Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		troi Device:
Spring Maximum Operating Temp: 250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		ding Mathad
Maximum Operating Temp: 250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nya all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		ang metrod.
250.0 degrees fahrenheit 2nd response Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nya all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		Operating Tomp
Connection Style: Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nya ull ends Shelf Life: N/a Unit Of Measure: 		
Plain (pipe) all ends Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nya all ends Shelf Life: N/a Unit Of Measure:	-	
Valve Operation Method: Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure:		-
Automatic Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure:		
Connection Type: Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 	-	
Threaded external pipe all ends Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 		
Mounting Position: Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 		
Horizontal or vertical Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: 		
Maximum Operating Pressure: 5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 	_	
5000.0 pounds per square inch single response Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 		
Thread Size: 0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 		
0.250 inches all ends Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: 	-	
Special Features: Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure:		
Cracking pressure 2 - 4 psi Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: 		
Material: Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: 	-	
Steel comp 416 seat Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Nyt all ends Shelf Life: N/a Unit Of Measure: 	-	pressure 2 - 4 psi
Material Specification: Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure:		440
Aisi 416 assn standard single material response body Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		
Media For Which Designed: Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: 		
Carbon dioxide 5th response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		
Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		-
Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:		·
Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:	-	-
Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization:	-	
Shelf Life: N/a Unit Of Measure: Demilitarization:		
N/a Unit Of Measure: Demilitarization:	-	
Unit Of Measure: Demilitarization:	Shelf Life	12
 Demilitarization:	N/a	
Demilitarization:	Unit Of N	easure:
No		ization:
	No	
Fiig:	Fiig:	