## NSN 4820-01-091-1305

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-091-1305 **Thread Direction:** Right-hand 1st end **Flow Control Device: Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.250 inches 2nd end **Opening Pressure Setting:** 5.0 pounds per square inch **Special Features:** 1.625 in. O/a length, 0.750 diameter hex body Material: Steel comp 303 **Material Specification:** Qq-s-763, class 303 federal specification single material response Media For Which Designed: Hydrazine single response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Npt 1st end Shelf Life:

N/a **Unit Of Measure:** 

## NSN 4820-01-091-1305

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0