## NSN 4820-01-091-7996

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-091-7996

1.500 inches all ends  Flow Control Device:  Disk  Disk Loading Method:  Weight  Renewable Seat Ring Type:  Retaining screw  Maximum Operating Temp:  500.0 degrees fahrenheit single response  Connection Style:  Socket (pipe) all ends  Valve Operation Method:  Automatic  Connection Type:  Unthreaded internal pipe all ends  Maximum Operating Pressure:  150.0 pounds per square inch single response  Special Features:  P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material:  Stainless steel seat  Material Specification:  Astma216, grade wcb assn standard single material response body  Media For Which Designed:  Water-oil-gas single response  Shelf Life:  N/a  Unit Of Measure:
Disk Loading Method: Weight Renewable Seat Ring Type: Retaining screw Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Disk Loading Method: Weight Renewable Seat Ring Type: Retaining screw Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Weight Renewable Seat Ring Type: Retaining screw Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Retaining screw  Maximum Operating Temp: 500.0 degrees fahrenheit single response  Connection Style: Socket (pipe) all ends  Valve Operation Method: Automatic  Connection Type: Unthreaded internal pipe all ends  Maximum Operating Pressure: 150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Retaining screw  Maximum Operating Temp: 500.0 degrees fahrenheit single response  Connection Style: Socket (pipe) all ends  Valve Operation Method: Automatic  Connection Type: Unthreaded internal pipe all ends  Maximum Operating Pressure: 150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Maximum Operating Temp: 500.0 degrees fahrenheit single response Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Connection Style: Socket (pipe) all ends Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Socket (pipe) all ends  Valve Operation Method: Automatic  Connection Type: Unthreaded internal pipe all ends  Maximum Operating Pressure: 150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Valve Operation Method: Automatic Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Automatic  Connection Type: Unthreaded internal pipe all ends  Maximum Operating Pressure: 150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 150.0 pounds per square inch single response Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150 Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Unthreaded internal pipe all ends  Maximum Operating Pressure:  150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Maximum Operating Pressure:  150.0 pounds per square inch single response  Special Features:  P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material:  Stainless steel seat  Material Specification:  Astma216, grade wcb assn standard single material response body  Media For Which Designed:  Water-oil-gas single response  Shelf Life:  N/a
150.0 pounds per square inch single response  Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Special Features: P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
P/n milv18436grpc, typeiii, trim5, socket welded 1 1/2in, class150  Material: Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Material: Stainless steel seat Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Stainless steel seat  Material Specification: Astma216, grade wcb assn standard single material response body  Media For Which Designed: Water-oil-gas single response  Shelf Life: N/a
Material Specification: Astma216, grade wcb assn standard single material response body Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Astma216, grade wcb assn standard single material response body  Media For Which Designed:  Water-oil-gas single response  Shelf Life:  N/a
Media For Which Designed: Water-oil-gas single response Shelf Life: N/a
Water-oil-gas single response  Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A530b0
Mil-std (military Standard):