

View Online at <https://aerobasegroup.com/nsn/4820-01-097-5907>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Threaded

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

End Application:

Anti-sub systems

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Adjustable Pressure Range:

+35.0/+44.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Opening Pressure Setting:

40.0 pounds per square inch

Outside Diameter:

6.625 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

6.000 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0