

View Online at <https://aerobasegroup.com/nsn/4820-01-099-6119>

Body Material:

Steel, federal standard 66, aisi 303/sae 30303

Outside Surface Treatment:

Passivated

Body Style:

Straight thru

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Outside Diameter Tube Accommodated:

0.750 inches

First End Thread Size And Series/type Designator:

1-1/16-12 un

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

Second End Outside Diameter Tube Accommodated:

0.500 inches

Second End Thread Size And Series/type Designator:

3/4-16 unf

Second End Thread Class:

2a

Second End Thread Direction:

Right-hand

First End Seat Angle In Deg:

37.0

Second End Seat Angle In Deg:

37.0

Flow Control Device:

Diaphragm

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Outlet Pressure Range:

+15.0/+95.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Weight

Maximum Inlet Pressure Rating:

150.0 pounds per square inch

Filter:

Not included

Temperature Rating:

Between -40.0 degrees fahrenheit and 150.0 degrees fahrenheit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100