NSN 4820-01-102-0962

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-102-0962

Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+72.0/+88.0 pounds per square inch
Outside Diameter:
4.250 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.625 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.625 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy body
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Or Standard:
B grade

NSN 4820-01-102-0962

Safety Relief Valve - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

Mil-std (military Standard):

Mil-v-24332 spec.