

View Online at <https://aerobasegroup.com/nsn/4820-01-103-8897>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Union

**Disk Loading Method:**

Spring

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

1.500 inches

**Adjustable Pressure Range:**

+18.0/+25.0 pounds per square inch

**Maximum Operating Pressure:**

275.0 pounds per square inch single response

**Outside Diameter:**

5.000 inches 2nd end

**Thickness:**

0.750 inches 1st end

**First Connection Face To Centerline Distance:**

4.875 inches

**Bolt Hole Diameter:**

0.750 inches 1st end

**Second Connection Face To Centerline Distance:**

5.125 inches

**Bolt Circle Diameter:**

6.000 inches 1st end

**Flange Face Design:**

Raised swivel 2nd end

**Raised Face Height:**

0.688 inches 2nd end

**Raised Face Diameter:**

5.000 inches 1st end

**Material:**

Stainless steel stem

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources, 15187 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Furnished Items And Quantity:**

1 lever

**Specification Data:**

81349-mil-v-24332 government specification

**Specification Or Standard:**

A grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0

**Mil-std (military Standard):**

Mil-v-24332 spec.