NSN 4820-01-105-9928

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-105-9928

Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
Adjustable i ressure Range.
+1401.0/+1500.0 pounds per square inch
•
+1401.0/+1500.0 pounds per square inch
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life: N/a
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life: N/a
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization:
+1401.0/+1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response Material: Nickel alloy flow control device Media For Which Designed: Gas, inert single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: Demilitarization: No