NSN 4820-01-107-4662

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-107-4662

Thread Class:
2a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Avenger class mcm
Connection Style:
Err-090 all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Thready Qty Per Inch (tpi):
11 all ends
Adjustable Pressure Range:
+28.0/+36.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Thread Size:
2.188 inches all ends
Seat Angle:
45.0 degrees all ends
Special Features:
Valve sz 0.750 in.
Material:
Stainless steel flow control device
Material Specification:
Qq-c-390, alloy, d4/d/ federal specification single material response body
Style Designator:
Err-090
Thread Series Designator:
Uns all ends

NSN 4820-01-107-4662

Safety Relief Valve - Page 2 of 2



Furnished	Items And	Quantity:
-----------	-----------	-----------

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0