NSN 4820-01-107-4662

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-107-4662

Thread Class:

2a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Maximum Operating Temp:

150.0 degrees fahrenheit single response

End Application:

Avenger class mcm

Connection Style:

Err-090 all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

11 all ends

Adjustable Pressure Range:

+28.0/+36.0 pounds per square inch

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thread Size:

2.188 inches all ends

Seat Angle:

45.0 degrees all ends

Special Features:

Valve sz 0.750 in.

Material:

Stainless steel flow control device

Material Specification:

Qq-c-390, alloy, d4/d/ federal specification single material response body

Style Designator:

Err-090

Thread Series Designator:

Uns all ends

NSN 4820-01-107-4662

Safety Relief Valve - Page 2 of 2



Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0