# NSN 4820-01-112-3895

Restrictor Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-112-3895

#### **Thread Class:**

3a 1st end

**Thread Direction:** 

Right-hand 1st end

# Flow Control Device:

Disk

#### **Connection Style:**

Flareless 2nd end

#### Valve Operation Method:

Automatic

#### Connection Type:

Threaded external tube 2nd end

## **Mounting Position:**

Horizontal

## Thready Qty Per Inch (tpi):

20 2nd end

## Maximum Operating Pressure:

1750.0 pounds per square inch single response

## **Thread Size:**

0.438 inches 1st end

## Seat Angle:

37.0 degrees 1st end

## **Special Features:**

One end with four slots spaced 90 degrees apart; square wrenching feature, with one 0.047 in. Diameter hole across each corner, 0.810 in.

Square across corner flats, with lockwire and nameplate tag through one corner hole

#### Material:

Steel comp 630

#### **Material Specification:**

Ams 5643 assn standard single material response

## Media For Which Designed:

Hydraulic fluid, petroleum base single response

#### Style Designator:

Straight thru

#### **Thread Series Designator:**

Unj 2nd end

# Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A530b0