NSN 4820-01-118-6863

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-118-6863

Body Material:
Steel
Body Style:
Straight thru
Media For Which Designed:
Hydrocarbon fuels and oils
First End Connection Type:
Plain face flange
First End Style Designator:
Plain
First End Flange Shape Style:
Rectangular (includes square) w/ bolt holes
First End Flange Thickness:
2.700 inches
First End Flange Length:
3.250 inches
First End Flange Width:
4.000 inches
First End Bolt Hole Quantity:
4
First End Bolt Hole Diameter:
0.406 inches
Second End Relationship With First End:
Identical
Center To Center Distance:
4.620 inches
Flow Control Device:
Piston, spring loaded
End Connection Quantity:
2
Valve Discharge Flow Rate:
30.0 gallons per minute
Maximum Inlet Pressure Rating:
2000.0 pounds per square inch
First End Center To Center Distance Between Holes Along Length:
2.375 inches
First End Center To Center Distance Between Holes Along Width:
3.125 inches
Tempurature Rating:
100.0 degrees fahrenheit
Shelf Life:
N/a

NSN 4820-01-118-6863

Calibrated Flow Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100