NSN 4820-01-118-6863

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-118-6863

| Body Material: |
|-----------------------------------------------------------------|
| Steel |
| |
| Body Style: Straight thru |
| |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| First End Connection Type: |
| Plain face flange |
| First End Style Designator: Plain |
| |
| First End Flange Shape Style: |
| Rectangular (includes square) w/ bolt holes |
| First End Flange Thickness: |
| 2.700 inches |
| First End Flange Length: |
| 3.250 inches |
| First End Flange Width: 4.000 inches |
| |
| First End Bolt Hole Quantity: |
| 4 First End Bolt Hole Diameter: |
| |
| 0.406 inches |
| Second End Relationship With First End: Identical |
| Center To Center Distance: |
| 4.620 inches |
| Flow Control Device: |
| Piston, spring loaded |
| End Connection Quantity: |
| 2 |
| Valve Discharge Flow Rate: |
| 30.0 gallons per minute |
| Maximum Inlet Pressure Rating: |
| 2000.0 pounds per square inch |
| First End Center To Center Distance Between Holes Along Length: |
| 2.375 inches |
| First End Center To Center Distance Between Holes Along Width: |
| 3.125 inches |
| Tempurature Rating: |
| 100.0 degrees fahrenheit |
| Shelf Life: |
| N/a |
| |

NSN 4820-01-118-6863

Calibrated Flow Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100

