NSN 4820-01-118-7351

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-118-7351

| Flow Control Device: |
|--|
| Disk |
| Disk Loading Method: |
| Weight |
| Renewable Seat Ring Type: |
| Threaded |
| Bolt Hole Quantity: |
| 4 all ends |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal or vertical |
| Valve Size: |
| 0.500 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 3.750 inches all ends |
| Face To Face Distance: |
| 6.000 inches |
| Thickness: |
| 0.440 inches all ends |
| Bolt Hole Diameter: |
| 0.625 inches all ends |
| Bolt Circle Diameter: |
| 2.625 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| 1.380 inches all ends |
| Special Features: |
| Swing check; end flanges iaw ansi b16.5, face to face dimensions iaw ansi b16.10 |
| Material: |
| Steel uns j92900 body |
| Material Specification: |
| Astm a351, grade cf8m assn standard single material response body |

NSN 4820-01-118-7351

Check Valve - Page 2 of 2



| Sty | e | De | si | ar | าลเ | to | r | • |
|-----|---|----|----|----|-----|----|---|---|
| · | • | | v. | 9. | | | • | • |

Straight through flanged ends

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 48422 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0