## NSN 4820-01-121-0845

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-121-0845

Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
End Application:
Ship, ohio class ss (trident)
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.000 inches
Adjustable Pressure Range:
+106.0/+120.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
4.250 inches all ends
Thickness:
0.375 inches all ends
First Connection Face To Centerline Distance:
3.500 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.500 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Plain 1st end
Material:
Nickel alloy flow control device
Media For Which Designed:
Water-oil-gas single response

## NSN 4820-01-121-0845

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A046b0