

View Online at <https://aerobasegroup.com/nsn/4820-01-121-8056>

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 2nd end

Maximum Operating Temp:

450.0 degrees fahrenheit single response

End Application:

Used on condensate tank onboard 270 ft wmec cg vessels

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Threaded internal pipe 1st end

Valve Size:

4.000 inches

Maximum Operating Pressure:

30.0 pounds per square inch single response

Thread Size:

4.000 inches 1st end

Outside Diameter:

7.000 inches 2nd end

Thickness:

0.687 inches 2nd end

First Connection Face To Centerline Distance:

5.250 inches

Bolt Hole Diameter:

0.625 inches 2nd end

Second Connection Face To Centerline Distance:

5.500 inches

Bolt Circle Diameter:

5.875 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.062 inches 2nd end

Raised Face Diameter:

4.687 inches 2nd end

Material:

Iron cast body

Style Designator:

Angle flanged ends

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0