NSN 4820-01-121-8058

Safety Relief Valve - Page 1 of 2

Thread Direction:
Right-hand 1st end
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-121-8058

Disk
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
End Application:
Condensate tank onboard 270 ft wmec cg vessels
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Threaded internal pipe 1st end
Valve Size:
3.000 inches
Thread Size:
3.000 inches 1st end
Outside Diameter:
6.000 inches 2nd end
Thickness:
0.625 inches 2nd end
First Connection Face To Centerline Distance:
4.250 inches
Bolt Hole Diameter:
0.625 inches 2nd end
Second Connection Face To Centerline Distance:
4.375 inches
Bolt Circle Diameter:
4.750 inches 2nd end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 2nd end
0.062 inches 2nd end Raised Face Diameter:
Raised Face Diameter:
Raised Face Diameter: 4.062 inches 2nd end

NSN 4820-01-121-8058

Safety Relief Valve - Page 2 of 2



Style	Design	ator:

Angle flanged ends

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0