

View Online at <https://aerobasegroup.com/nsn/4820-01-122-8064>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

450.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

1.500 inches

**Maximum Operating Pressure:**

300.0 pounds per square inch 1st response

**Outside Diameter:**

5.000 inches all ends

**Thickness:**

0.438 inches all ends

**First Connection Face To Centerline Distance:**

3.125 inches

**Bolt Hole Diameter:**

0.625 inches all ends

**Second Connection Face To Centerline Distance:**

3.125 inches

**Bolt Circle Diameter:**

3.875 inches all ends

**Flange Face Design:**

Plain all ends

**Special Features:**

Stop-check valve internally

**Material Specification:**

Astm b61 assn standard single material response flow control device or astm b62 assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources, 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0