

View Online at <https://aerobasegroup.com/nsn/4820-01-122-8064>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

450.0 degrees fahrenheit 1st response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

300.0 pounds per square inch 1st response

Outside Diameter:

5.000 inches all ends

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

3.125 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

3.125 inches

Bolt Circle Diameter:

3.875 inches all ends

Flange Face Design:

Plain all ends

Special Features:

Stop-check valve internally

Material Specification:

Astm b61 assn standard single material response flow control device or astm b62 assn standard single material response flow control device

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 30263 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0