

View Online at <https://aerobasegroup.com/nsn/4820-01-123-2901>

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

5.0 gallons per minute

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Minimum Operating Temp:

-65.0 degrees fahrenheit

Connection Style:

G46b plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.125 inches 1st end

Opening Pressure Setting:

130.0 pounds per square inch

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, alloy 2024, t351 federal specification single material response

Media For Which Designed:

Oxygen, gaseous 3rd response

Surface Treatment:

Anodize and chromate

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0