## NSN 4820-01-123-2901

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-123-2901

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
5.0 gallons per minute
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Minimum Operating Temp:
-65.0 degrees fahrenheit
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches 1st end
Opening Pressure Setting:
130.0 pounds per square inch
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, alloy 2024, t351 federal specification single material response
Media For Which Designed:
Oxygen, gaseous 3rd response
Surface Treatment:
Anodize and chromate
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:

1 deflector cap

## NSN 4820-01-123-2901

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0